

TECHNICAL DATA SHEET



LONG OIL ALKYD RESIN

ALKYD LO-1555 WS

FEATURES

- Fast drying
- Good Gloss
- Good Hardness

APPLICATION

- Decorative enamels

CHARACTERISTICS

- | | |
|-----------------------------------|--------------|
| • Oil Length | 52 % |
| • Solvent | White Spirit |
| • Oil type | Soya |
| • Solid Content (% by wt) | 55 ± 1% |
| • Viscosity (Gardner scale @25°C) | U – V |
| • Acid Value on solids(mg KOH/g) | < 15 |
| • Color (Gardner 1933) | 5 max |

SOLUBILITY DATA

- | | |
|-------------------------|---------|
| • Aromatic Hydrocarbons | Soluble |
| • White Spirits | Soluble |
| • Alcohols | Soluble |
| • Esters | Soluble |
| • Ketones | Soluble |

COMPATIBILITY DATA

- | | |
|---------------------|--------------|
| • Medium oil Alkyds | Compatible |
| • Short Oil Alkyds | Incompatible |

DELIVERY FORM DETAILS

- Mild steel drums (Net .Weight 190 Kg)

SHELF LIFE:

- Minimum 12 months in original unopened containers stored between 5 and 35 °C

Disclaimer (Updated On March 2013)

DISCLAIMER

This information contained in the data sheet is to the best of our knowledge correct and up to date. Under well-defined conditions. Its accuracy or suitability under the actual conditions of any independent use is not guaranteed and must be determined by the user. All advice given about this product is given in good faith. Since as we have no control over conditions of substrate, manufacturer and seller cannot accept any liability in connection with the use of the product relative to coverage, performance, injury, or damage, unless we specify in writing to do so. The information in this data sheet is subject to change without prior notice and it is the user responsibility to ensure it is current. For further information and advice please contact UCC Technical Service Department.