

# TECHNICAL DATA SHEET



## LONG OIL ALKYD RESIN

## ALKYD LO-1704 WS

### FEATURES

- High Brushability, Good Gloss retention
- Low Viscosity
- Good Adhesive & mechanical properties
- Excellent for economical enamel pigmented

### APPLICATION

- Decorative Enamel Paints for internal and external Applications

### CHARACTERISTICS

- |   |                    |
|---|--------------------|
| • Oil Length                              | 59 %               |
| • Solvent                                 | White Spirit       |
| • Oil type                                | SOFA               |
| • Solid Content ( % by wt)                | 70 ± 1%            |
| • Viscosity(B/F,25°C@70%,20rpm,spindle 5) | 130ps – 160ps      |
| • Acid Value                              | < 15 mg KOH/ g     |
| • OH value(on Solids)                     | 1.9 – 2.0 mg KOH/g |
| • Color (Gardner @ 50%)                   | 5 max              |

### SOLUBILITY DATA

- |                      |         |
|----------------------|---------|
| • Aliphatic Solvents | Soluble |
| • Alcohols           | Soluble |
| • Esters             | Soluble |
| • Ketones            | Soluble |

### COMPATIBILITY DATA

- |                    |              |
|--------------------|--------------|
| • Medium oil Alkyd | Compatible   |
| • Short Oil Alkyd  | Incompatible |
| • Rosin maleate    | Compatible   |

### DELIVERY FORM DETAILS

- 70% in White Spirit - Bulk & 70% in White Spirit - Drums (190 kg / drum)

### SHELF LIFE:

- minimum 12 months when stored under standard storage conditions

Disclaimer (Updated On March 2013)

#### DISCLAIMER

This information contained in the data sheet is to the best of our knowledge correct and up to date. Under well-defined conditions. Its accuracy or suitability under the actual conditions of any independent use is not guaranteed and must be determined by the user. All advice given about this product is given in good faith. Since as we have no control over conditions of substrate, manufacturer and seller cannot accept any liability in connection with the use of the product relative to coverage, performance, injury, or damage, unless we specify in writing to do so. The information in this data sheet is subject to change without prior notice and it is the user responsibility to ensure it is current. For further information and advice please contact UCC Technical Service Department.